Under the Paperwork Reduction Act of 1995, no persons  TRANSMITTAL  FORM			s are required to respond to a c Application Number Filing Date	10/792,01 March 2,	Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCI llection of information unless it displays a valid OMB control numbe 10/792,018  March 2, 2004			
			Art Unit Examiner Name	2611	Mark Lampinen, et al 2611  Kevin Michael Burd			
(to be used for all correspondence after initial filing)  Total Number of Pages in This Submission			Attorney Docket Number		944-005.027			
<del></del>		ENC	LOSURES (Check a	II that appl	у)			
Amendm A A Extension Express Information Certified Documer Reply to Incomple	ee Attached ent/Reply fiter Final ffidavits/declaration(s) n of Time Request Abandonment Request on Disclosure Statement Copy of Priority nt(s) Missing Parts/ te Application teply to Missing Parts nder 37 CFR 1.52 or 1.53		Drawing(s)  Licensing-related Papers  Petition  Petition to Convert to a  Provisional Application  Power of Attorney, Revocat  Change of Correspondence  Terminal Disclaimer  Request for Refund  CD, Number of CD(s)  Landscape Table on Coks	Address	Appeal Communication to Board of Appeals and Interferences  Appeal Communication to TC (Appeal Notice, Brief, Reply Brief)  Proprietary Information  Status Letter Other Enclosure(s) (please Identify below):			
Firm Name	SIGNA	TURE C	OF APPLICANT, ATTO	ORNEY, (	OR AGENT			
Signature	Ware, Fressola, Van Der	Sluys & A	dolphson, LLP					
Printed name Kenneth Q. Lao								
Date December 1 4 , 2007				Reg. No.	O. 40,061			

This collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and1.14. This collection is estimated to 2 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

Marie É. Forte

Typed or printed name

December 12, 2007

Date

PTO/SB/17 (10-07)

Approved for use through 06/30/2010. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE U.S. Patent and Tragemark Office, U.S. Der Commission School of University of the Haperwork Reduction Act of 1995 no persons are required to respond to a collection of information unless it displays a valid OMB control number

Complete if Known Effective on 12/08/2004. Fees pursuant to the Consolidated Appropriations Act, 2005 (H.R. 4818). **Application Number** 10/792,018 RANSMIT Filing Date March 2, 2004 For FY 2008 First Named Inventor Marko Lampinen **Examiner Name** Kevin Michael Burd Applicant claims small entity status. See 37 CFR 1.27 Art Unit 2611

TOTAL AMOUNT OF PAYE	(a)	510.00		Attorney Docket	No.   944	1-005.027					
METHOD OF PAYMENT (check all that apply)											
Check Credit Card Money Order None Other (please identify):  Deposit Account Deposit Account Number: 23-0442 Deposit Account Name:  For the above-identified deposit account, the Director is hereby authorized to: (check all that apply)  Charge fee(s) indicated below Charge fee(s) indicated below, except for the filing fee  Charge any additional fee(s) or underpayments of fee(s) Credit any overpayments  WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.											
FEE CALCULATION											
1. BASIC FILING, SEAR	ATION FEES Small Entity										
Application Type	Fee (\$)	Fee (\$)	Fee (\$)		Fee (\$)	<u>Fee (\$)</u>	Fees Paid (\$)				
Utility	310	155	510	255	210	105					
Design	210	105	100	50	130	65					
Plant	210	105	310	155	160	80					
Reissue	310	155	510	255	620	310					
Provisional	210	105	0	0	0	0					
2. EXCESS CLAIM FEES  Fee Description  Each claim over 20 (including Reissues)  Each independent claim over 3 (including Reissues)  Multiple dependent claims  Total Claims  Extra Claims Fee (\$) Fee Paid (\$)  — -20 or HP = x =  HP = highest number of total claims paid for, if greater than 20.  Indep. Claims Extra Claims Fee (\$) Fee Paid (\$)  — -3 or HP = x =  HP = highest number of independent claims paid for, if greater than 3.											
3. APPLICATION SIZE FEE  If the specification and drawings exceed 100 sheets of paper (excluding electronically filed sequence or computer listings under 37 CFR 1.52(e)), the application size fee due is \$260 (\$130 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).  Total Sheets  Extra Sheets  Number of each additional 50 or fraction thereof  - 100 = /50 = (round up to a whole number) x = Fee (\$)  4. OTHER FEE(S)  Non-English Specification, \$130 fee (no small entity discount)											
Other (e.g., late filing surcharge): Appeal Brief Filing Fee											

SUBMITTED BY Registration No. (Attorney/Agent) 40,061 Telephone 203-261-1234 Signature Date December 14, 2007 Name (Print/Type) Kenneth Q. Lao

This collection of information is required by 37 CFR 1.136. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 30 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

Serial Number: 10/792,018

### IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: LAMPINEN, el al

Application No.: 10/792,018

Group No.: 2611

Filed: March 2, 2004

Examiner: Kevin Michael Burd

For: CPICH PROCESSING FOR SINR ESTIMATION IN W-CDMA SYSTEM

Mail Stop Appeal Brief - Patents Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

## BRIEF OF APPELLANTS (37 CFR §41.37)

Sir:

This is an appeal from the final rejection contained in a Final Office Action mailed on July 20, 2007 (the "Final Office Action"), rejecting claims 3-7, 9-12, 14-18 and 20-25.

\*\*\*If any fee and/or extension is required in addition to any enclosed herewith, please charge Account No. <u>23-0442</u>.

# CERTIFICATE OF MAILING/TRANSMISSION (37 C.F.R. § 1.8(a))

I hereby certify that this correspondence is, on the date shown below, being:

MAILING

**FACSIMILE** 

□ Deposited with the United States Postal
Service with sufficient postage as first class
Mail in an envelope addressed to the

Mail in an envelope addressed to the Commissioner for Patents, PO Box 1450,

Alexandria, VA 22313-1450.

☐ Transmitted by facsimile to the U.S. Patent and

Trademark Office.

Date: December 14,2007

Signature

(type or print name of person certifying)

61 FC: 1482

510.00 OP

Serial Number: 10/792,018

#### I. REAL PARTY IN INTEREST (37 CFR §41.37(c)(1)(i))

The real party in interest in this action is Nokia Corporation, Keilalahdentie 4, FIN-02150 Espoo, Finland, by virtue of the Assignment dated November 10 and 14, 2003. The Assignment was recorded in the U.S. Patent and Trademark Office on February 9, 2004.

# II. RELATED APPEALS AND INTERFERENCES (37 CFR §41.37(c)(1)(ii)) There are no related appeals or interferences.

#### III. STATUS OF CLAIMS (37 CFR§41.37(c)(1)(iii))

The status of the claims is:

Claims pending: 3-7, 9-12, 14-18 and 20-25.

Claims objected to: none.

Claims rejected: 3-7, 9-12, 14-18 and 20-25.

Claims on appeal: 3-7, 9-12, 14-18 and 20-25.

#### IV. STATUS OF AMENDMENTS (37 CFR §41.37(c)(1)(iv))

No amendment as to claims 3-7, 9-12, 14-18 and 20-25 has been filed subsequent to final rejection.

#### V. SUMMARY OF CLAIMED SUBJECT MATTER (37 CFR §41.37(c)(1)(v))

Appellant's invention is directed to a method and system for estimating the signal to signal-to-interference plus noise ratio of the common pilot channel in a wideband code-division multiple access receiver. The ratio estimation is carried out after chip leel filtering and then the despreading of the common pilot channel. In particular, space-time transmit diversity is used in the transmission of signals and the power from each of the transmit antennas is combined for obtaining the received common pilot channel. See page 6, lines 13 to 23.

Serial Number: 10/792,018

The invention of claim 3 is directed to a method for estimating the signal-to-inteference ratio in a receiver having an equalization stage for chip level filtering of received chip. The method includes the following steps:

- 1. Despreading a common pilot channel in a spread-spectrum receiver adapted to receive a signal stream in space-time diversity transmission, wherein the despreading is carried out after the chip level filtering (page 6, lines 6-9); and
- 2. Estimating the signal-to-interference ratio from the despread common pilot channel symbols (page 6, lines 9-12).

The invention of dependent claim 4 is directed to the method in which a virtual space-time decoding is used on the common pilot channel in order to mimic data channel space-time transformation (page 9, lines 8-10).

The invention of dependent claim 5 is directed to the method in which the received chips are oversampled at chip-level (page 7, lines 6-9).

The invention of claim 6 is directed to a receiver, which includes:

- 1. An equalization stage for chip level filtering received chips, wherein the received chips are obtained from a signal stream in space-time transmit diversity transmission;
- A despreading module for despreading a common pilot channel after said chip level filtering; and
- 3. An estimation module for estimating signal-to-interference ratio at least partially from despread common pilot channel symbols. *See* Figure 2.

The invention of dependent claim 7 is directed to the receiver wherein the estimated signal-to-interference ratio is for use by a user equipment in the communications system to report its channel quality indicator (page 1, lines 19-26).

Serial Number: 10/792,018

The invention of dependent claim 9 is directed to the receiver in a communications system having a transmitter with space-time transmit diversity transmission (Figure 2; page 6, lines 13-21).

The invention of dependent claim 10 is directed to the receiver in the communications system wherein the received chips are over-sampled at chip level (page 7, lines 6-9).

The invention of claim 11 is directed to a spread-spectrum communications system, which includes:

a receiver; and

a transmitter for transmitting a signal stream in space-time transmit diversity transmission to the receiver, the signal stream containing a chip stream in a common pilot channel, wherein the receiver has at least one antenna to receive one or more chips in the chip stream; wherein the receiver includes:

an equalization stage for chip level filtering the received chips;

a despreading module for despreading the common pilot channel after said chip level filtering; and

an estimation module for estimating signal-to-interference ratio at least partially from despread common pilot channel symbols. See Figure 2 and page 6, lines 13-21.

The invention of dependent claim 12 is directed to the communications system in which the estimated signal-to-interference ratio is for use by a user equipment in the communications system to report its channel quality indicator (page 1, lines 19-26).

The invention of dependent claim 14 is directed to the communications system in which the transmitter has two or more antennas for transmitting the signal stream in order to achieve space-time transmit diversity (Figure 2; page 6, lines 13-21).

The invention of dependent claim 15 is directed to the communications system in which the received chips are over-sampled at chip level (page 7, lines 6-9).

The invention of dependent claims 16 is directed to the communications system wherein a virtual space-time decoding in the receiver is used on the common pilot channel in order to mimic data channel space-time transformation (page 9, lines 8-10).

The invention of claim 17 is directed to a communications device in a communications system. The device includes:

an antenna; and

a receiver, operatively connected to the antenna, for receiving communication signals in space-time transmit diversity transmission, wherein the communication signals include a transmitted signal indicative of one or more chips in a chip stream in a common pilot channel; and wherein the received signals include received chips, the receiver including:

an equalization stage for chip level filtering received chips;

a despreading module for despreading a common pilot channel after said chip level filtering; and

an estimation module for estimating signal-to-interference ratio at least partially from despread symbols (Figure 2; page 6, lines 13-21).

The invention of dependent claim 18 is directed to the communications device in which the estimated signal-to-interference ratio is used for reporting a channel quality indicator to another component in the communication system (page 1, lines 19-26).

The invention of dependent claim 20 is directed to the communications device in which the communications signals are transmitted from a transmitter having two or more antennas for transmitting the signal stream in order to achieve the space-time transmit diversity transmission (Figure 2; page 6, lines 13-21).

The invention of dependent claim 21 is directed to the communication device including a mobile terminal (page 10, lines 1-6).

Serial Number: 10/792,018

The invention of dependent claim 22 is directed to the communications system including a wideband code division multiple access communications system (page 9, lines 27-28).

The invention of dependent claim 23 is directed to the method in which the spread-spectrum receiver comprises a wideband code division multiple access receiver (page 9, lines 24-27).

The invention of claim 24 is directed to a spread-spectrum communications system, which includes:

a receiver; and

means for transmitting a signal stream to the receiver in space-time transmit diversity transmission, the signal stream containing a chip stream in a common pilot channel, wherein the receiver has at least one antenna to receive one or more chips in the chip stream; the receiver further including:

means for chip level filtering the received chips;

means for despreading the common pilot channel after said chip level filtering; and

means for estimating signal-to-interference ratio at least partially from despread common pilot channel symbols (Figure 2; page 6, lines 13-21).

The invention of dependent claim 25 is directed to a communications system in which the estimated signal-to-interference ratio is for use by a user equipment in the communications system to report its channel quality indicator (page 1, lines 19-26).

# VI. GROUNDS OF REJECTION TO BE REVIEWED ON APPEAL (37 CFR §41.37(c)(1)(vi))

Claims 3-7, 9-12, 14-18 and 20-25 are rejected under 35 U.S.C. 103(a) as being unpatentable over *Petre et al.* (U.S. Patent No. 7,158,558), in view of *Onggosanusi et al.* (U.S. Patent Application Publication No. 2002/0196842, *Onggosanusi*).

#### VII. ARGUMENT (37 CFR §41.37(c)(1)(vii))

At section 3, claims 3-7, 9-12, 14-18 and 20-25 are rejected under 35 U.S.C. 103(a) as being unpatentable over *Petre et al.* (U.S. Patent No. 7,158,558, hereafter referred to as *Petre*), in view of *Onggosanusi et al.* (U.S. Patent Application Publication No. 2002/0196842, hereafter referred to as *Onggosanusi*).

#### (A) Claim 3

The invention as claimed in independent claim 3 includes the limitation of despreading a Common Pilot Channel in a spread-spectrum receiver, wherein the spread-spectrum receiver is adapted to receive a signal stream in space-time diversity transmission.

In rejecting claim 3, the Examiner states that *Petre* discloses a method of communication using a common pilot channel (CPICH) in a W-CDMA receiver which receives the CPICH. The signal is equalized using chip level equalization and the equalized CPICH channel is despread. The Examiner admits that *Petre* fails to disclose estimating SINR from the despread CPICH, but points to *Onggosanusi* for disclosing that feature.

The Examiner states that *Onggosanusi* discloses estimating the signal-to-interference ratio (SINR) from the despread CPICH. The Examiner also states that *Onggosanusi* discloses that the transmitter comprises multiple antennas (Figure 3 and paragraph [0049]). The Examiner is **silent** on whether *Onggosanusi* discloses the signal stream is the form for space-time transmit diversity transmission.

While it is true that *Onggosanusi* discloses a communications system having a number of transmit antennas as shown in Figures 1 to 4, the multiple transmit antenna system is used in a <u>multi-input multi-output</u> (MIMO) system. (see paragraphs [0008], [0009], [0013], [0016], [0049], [0062]). In one of the embodiments, *Onggosanusi* uses four transmit antennas TAT"<sub>1</sub> to TAT"<sub>4</sub> and a larger number of receive antennas RAT"<sub>1</sub> to RAT"<sub>Q</sub> (Q>4) in a MIMO system with double space-time block coded transmit antenna diversity (DSTTD). In this DSTTD system, *Onggosanusi* uses two STTD encoders to combine information multiplexing with transmit diversity MIMO.

Serial Number: 10/792,018

It is respectfully submitted that a signal transmitted in a DSTTD system is different from a signal stream in the space-time transmit diversity transmission, because a DSTTD system applies information multiplexing into two STTD blocks. For example, one of the STTD blocks transmits symbols  $S_{1,1}$  and  $S_{1,2}$  and the other STTD block transmits symbols  $S_{2,1}$  and  $S_{2,2}$  (see paragraph [0083]) The spatially parallel transmission causes additional interference. This interference would not be correctly taken into account by the claimed pilot processing for the space-time transmit diversity transmission scheme. Thus, the DSTTD scheme in Onggosanusi is not applicable for space-time transmit diversity transmission. Likewise, the claimed invention is not applicable for the DSTTD transmission.

Petre does not disclose that the signal stream is in the form for space-time transmit diversity transmission. Onggosanusi does not disclose that the signal stream is in the form for space-time transmit diversity transmission.

For the above reasons, *Petre*, in view of *Onggosanusi*, fails to render claim 3 obvious.

#### (B) Claim 6

The invention as claimed in independent claim 6 includes the limitation of an equalization stage for chip level filtering the received chips, wherein the received chips are obtained from a signal stream in space-time diversity transmission.

In rejecting claim 6, the Examiner states that *Petre* discloses a method of communication using a common pilot channel (CPICH) in a W-CDMA receiver which receives the CPICH. The signal is equalized using chip level equalization and the equalized CPICH channel is despread. The Examiner admits that *Petre* fails to disclose estimating SINR from the despread CPICH, but points to *Onggosanusi* for disclosing that feature.

The Examiner states that *Onggosanusi* discloses estimating the signal-to-interference ratio (SINR) from the despread CPICH. The Examiner also states that *Onggosanusi* discloses that the transmitter comprises multiple antennas (Figure 3 and paragraph [0049]). The Examiner is **silent** on whether *Onggosanusi* discloses the signal stream is the form for space-time transmit diversity transmission.

Serial Number: 10/792,018

As explained in sub-section B above, a signal transmitted in a DSTTD system is <u>different</u> from a signal stream in the space-time transmit diversity transmission, because a DSTTD system applies information multiplexing into two STTD blocks. The DSTTD scheme in *Onggosanusi* is not applicable for space-time transmit diversity transmission. Likewise, the claimed invention is not applicable for the DSTTD transmission.

Petre does not disclose that the signal stream is in the form for space-time transmit diversity transmission. Onggosanusi does not disclose that the signal stream is in the form for space-time transmit diversity transmission.

For the above reasons, *Petre*, in view of *Onggosanusi*, fails to render claim 6 obvious.

#### (C) Claim 11

The invention as claimed in independent claim 11 has the limitation of a transmitter for transmitting a signal stream in <u>space-time transmit diversity transmission</u> to a receiver.

In rejecting claim 11, the Examiner states that *Petre* discloses a method of communication using a common pilot channel (CPICH) in a W-CDMA receiver which receives the CPICH. The signal is equalized using chip level equalization and the equalized CPICH channel is despread. The Examiner admits that *Petre* fails to disclose estimating SINR from the despread CPICH, but points to *Onggosanusi* for disclosing that feature.

The Examiner states that *Onggosanusi* discloses estimating the signal-to-interference ratio (SINR) from the despread CPICH. The Examiner also states that *Onggosanusi* discloses that the transmitter comprises multiple antennas (Figure 3 and paragraph [0049]). The Examiner is **silent** on whether *Onggosanusi* discloses the signal stream is the form for space-time transmit diversity transmission.

As explained in sub-section B above, a signal transmitted in a DSTTD system is **different** from a signal stream in the space-time transmit diversity transmission, because a DSTTD system applies information multiplexing into two STTD blocks. The DSTTD scheme in *Onggosanusi* is not applicable for space-time transmit diversity transmission. Likewise, the claimed invention is not applicable for the DSTTD transmission.

Serial Number: 10/792,018

Petre does not disclose that the signal stream is in the form for space-time transmit diversity transmission. Onggosanusi does not disclose that the signal stream is in the form for space-time transmit diversity transmission.

For the above reasons, *Petre*, in view of *Onggosanusi*, fails to render claim 11 obvious.

#### (D) Claim 17

The invention as claimed in independent claim 17 has the limitation of a receiver for receiving communication signals in space-time diversity transmission.

In rejecting claim 17, the Examiner states that *Petre* discloses a method of communication using a common pilot channel (CPICH) in a W-CDMA receiver which receives the CPICH. The signal is equalized using chip level equalization and the equalized CPICH channel is despread. The Examiner admits that *Petre* fails to disclose estimating SINR from the despread CPICH, but points to *Onggosanusi* for disclosing that feature.

The Examiner states that *Onggosanusi* discloses estimating the signal-to-interference ratio (SINR) from the despread CPICH. The Examiner also states that *Onggosanusi* discloses that the transmitter comprises multiple antennas (Figure 3 and paragraph [0049]). The Examiner is **silent** on whether *Onggosanusi* discloses the signal stream is the form for space-time transmit diversity transmission.

As explained in sub-section B above, a signal transmitted in a DSTTD system is <u>different</u> from a signal stream in the space-time transmit diversity transmission, because a DSTTD system applies information multiplexing into two STTD blocks. The DSTTD scheme in *Onggosanusi* is not applicable for space-time transmit diversity transmission. Likewise, the claimed invention is not applicable for the DSTTD transmission.

Petre does not disclose that the signal stream is in the form for space-time transmit diversity transmission. Onggosanusi does not disclose that the signal stream is in the form for space-time transmit diversity transmission.

For the above reasons, *Petre*, in view of *Onggosanusi*, fails to render claim 17 obvious.

#### (E) Claim 24

The invention as claimed in independent claim 24 has the limitation of having means for transmitting a signal stream to a receiver in space-time diversity transmission.

In rejecting claim 24, the Examiner states that *Petre* discloses a method of communication using a common pilot channel (CPICH) in a W-CDMA receiver which receives the CPICH. The signal is equalized using chip level equalization and the equalized CPICH channel is despread. The Examiner admits that *Petre* fails to disclose estimating SINR from the despread CPICH, but points to *Onggosanusi* for disclosing that feature.

The Examiner states that *Onggosanusi* discloses estimating the signal-to-interference ratio (SINR) from the despread CPICH. The Examiner also states that *Onggosanusi* discloses that the transmitter comprises multiple antennas (Figure 3 and paragraph [0049]). The Examiner is **silent** on whether *Onggosanusi* discloses the signal stream is the form for space-time transmit diversity transmission.

As explained in sub-section B above, a signal transmitted in a DSTTD system is <u>different</u> from a signal stream in the space-time transmit diversity transmission, because a DSTTD system applies information multiplexing into two STTD blocks. The DSTTD scheme in *Onggosanusi* is not applicable for space-time transmit diversity transmission. Likewise, the claimed invention is not applicable for the DSTTD transmission.

Petre does not disclose that the signal stream is in the form for space-time transmit diversity transmission. Onggosanusi does not disclose that the signal stream is in the form for space-time transmit diversity transmission.

For the above reasons, *Petre*, in view of *Onggosanusi*, fails to render claim 24. obvious.

#### (F) Claims 4 and 16

The invention of claims 4 and 16 has the further limitation of using a virtual space-time decoding used on the CPICH channel in order to mimic data channel space-time transformation.

In rejecting claims 4 and 16, the Examiner states that the combination of the channel and receiver's chip level filtering at the equalizer can be seen as a virtual channel.

It is respectfully submitted that claims 4 and 16 are dependent from claims 3 and 11 and recite features not recited in claims 3 and 11. For reasons regarding claims 3 and 11 above, *Petre*, in view of *Onggosanusi*, also fails to render claims 4 and 16 obvious.

#### (G) Claims 5, 10 and 15

The invention as claimed in claims 5, 10 and 15 has the limitation that the received chips are over-sampled at chip level.

In rejecting claims 5, 10 and 15, the Examiner states that the combination of the teachings in *Petre* and *Onggosanusi* discloses that received chips are oversampled at chip-level.

It is respectfully submitted that claims 5, 10 and 15 are dependent from claims 3, 6 and 11 and recite features not recited in claims 3, 6 and 11. For reasons regarding claims 3, 6 and 11 above, *Petre*, in view of *Onggosanusi*, also fails to render claims 5, 10 and 15 obvious.

#### (H) Claim 21

The invention of claim 21 has the limitation that the receiver includes a mobile terminal.

In rejecting claim 21, the Examiner states that the receiver is in a mobile terminal.

It is respectfully submitted that claim 21 is dependent from claim 17 and recites features not recited in claim 21. For reasons regarding claim 21 above, *Petre*, in view of *Onggosanusi*, also fails to render claim 21 obvious.

#### (I) Claims 7, 9, 12, 14, 18, 20, 21, 22, 23 and 25

The Examiner rejects claims 7, 9, 12, 14, 18, 20, 21, 22, 23 and 25 on the same grounds as used in rejecting claims 3, 6, 11, 17 and 24.

It is respectfully submitted that claims 7, 9, 12, 14, 18, 20, 21, 22, 23 and 25 are dependent from claims 3, 6, 11, 17 and 24 and recite features not recited in claims 3, 6,

Serial Number: 10/792,018

11, 17 and 24. For reasons regarding claims 3, 6, 11, 17 and 24 above, *Petre*, in view of *Onggosanusi*, also fails to render claims 7, 9, 12, 14, 18, 20, 21, 22, 23 and 25 obvious.

#### VIII CLAIMS APPENDIX (37 CFR §41.37(c)(1)(viii))

### 3. A method, comprising:

despreading a Common Pilot Channel (CPICH) channel in a spread-spectrum receiver, wherein the spread-spectrum receiver is adapted to receive a signal stream in space-time diversity transmission and the receiver comprises an equalization stage for chip level filtering of received chip, and wherein said despreading is carried out after said chip level filtering; and

estimating the signal to interference ratio at least partially from despread CPICH symbols.

- 4. A method according to claim 3, wherein a virtual space-time decoding is used on the CPICH channel in order to mimic data channel space-time transformation
- 5. A method according to claim 3, wherein the received chips are oversampled at chip-level.

#### 6. A receiver, comprising:

an equalization stage for chip level filtering received chips, wherein the received chips are obtained from a signal stream in space-time transmit diversity transmission;

a despreading module for despreading a common pilot channel (CPICH) after said chip level filtering; and

an estimation module for estimating signal-to-interference ratio at least partially from despread CPICH symbols.

Serial Number: 10/792,018

7. A receiver according to claim 6, wherein the estimated signal-to-interference ratio is for use by a user equipment in the communications system to report its channel quality indicator (CQI).

- 9. A receiver according to claim 6, wherein the communications system comprises a transmitter with space-time transmit diversity transmission.
- 10. A receiver according to claim 9, wherein the received chips are over-sampled at chip level.
- 11. A spread-spectrum communications system comprising:

a receiver; and

a transmitter for transmitting a signal stream in space-time transmit diversity transmission to the receiver, the signal stream containing a chip stream in a common pilot channel (CPICH), wherein the receiver has at least one antenna to receive one or more chips in the chip stream; the receiver further comprising:

an equalization stage for chip level filtering the received chips;

a despreading module for despreading the common pilot channel after said chip level filtering; and

an estimation module for estimating signal-to-interference ratio at least partially from despread CPICH symbols.

- 12. A communications system according to claim 11, wherein the estimated signal-to-interference ratio is for use by a user equipment in the communications system to report its channel quality indicator (CQI).
- 14. A communications system according to claim 11, wherein the transmitter has two or more antennas for transmitting the signal stream in order to achieve space-time transmit diversity.

Serial Number: 10/792,018

15. A communications system according to claim 14, wherein the received chips are over-sampled at chip level.

- 16. A communications system according to claim 14, wherein a virtual space-time decoding in the receiver is used on the CPICH in order to mimic data channel space-time transformation.
- 17. A communications device in a communications system, comprising: an antenna; and

a receiver, operatively connected to the antenna, for receiving communication signals in space-time transmit diversity transmission, wherein the communication signals include a transmitted signal indicative of one or more chips in a chip stream in a common pilot channel (CPICH); and wherein the received signals include received chips, the receiver comprising:

an equalization stage for chip level filtering received chips;

a despreading module for despreading a common pilot channel (CPICH) after said chip level filtering; and

an estimation module for estimating signal-to-interference ratio at least partially from despread CPICH symbols.

- 18. A communications device according to claim 17, wherein the estimated signal-to-interference ratio is used for reporting a channel quality indicator (CQI) to another component in the communication system.
- 20. A communications device according to claim 17, wherein the communications signals are transmitted from a transmitter having two or more antennas for transmitting the signal stream in order to achieve the space-time transmit diversity transmission.
- 21. A communications device according to claim 17, comprising a mobile terminal.

Serial Number: 10/792,018

22. A communications system according to claim 11, comprising a W-CDMA communications system.

- 23. A method according to claim 3, wherein the spread-spectrum receiver comprises a W-CDMA receiver.
- 24. A spread-spectrum communications system comprising:

a receiver; and

means for transmitting a signal stream to the receiver in space-time transmit diversity transmission, the signal stream containing a chip stream in a common pilot channel (CPICH), wherein the receiver has at least one antenna to receive one or more chips in the chip stream; the receiver further comprising:

means for chip level filtering the received chips;

means for despreading the common pilot channel after said chip level filtering;

and

means for estimating signal-to-interference ratio at least partially from despread CPICH symbols.

25. A communications system according to claim 24, wherein the estimated signal-to-interference ratio is for use by a user equipment in the communications system to report its channel quality indicator (CQI).

Serial Number: 10/792,018

# IX. EVIDENCE APPENDIX (37 CFR §41.37(c)(1)(ix))

There are no evidences submitted pursuant to 37 CFR §1.130, 1,131 or 1,132.

# X. RELATED PROCEEDING APPENDIX (37 CFR §41.37(c)(1)(x))

There are no prior decisions rendered by a court or the Board in any proceeding identified pursuant to 37 CFR §41.37(c)(1)(ii).

Serial Number: 10/792,018

#### CONCLUSION

It is respectfully submitted that the present invention as claimed is readily distinguishable over the cited references.

Respectfully submitted,

Date: <u>December 14, 2007</u>

Kenneth Q. Lao Attorney for the Applicant Registration No. 40,061

WARE, FRESSOLA, VAN DER SLUYS & ADOLPHSON LLP

Bradford Green, Building Five 755 Main Street, P.O. Box 224 Monroe, CT 06468

Telephone: (203) 261-1234 Facsimile: (203) 261-5676

USPTO Customer No. 004955